








Row.	Product Image	Code	Description	PRICE(\$)
1		Akuvox X915	High-end Smart Door Phone 1.Size: 350x130x53,9mm (HxWxD) 2.Body material: 316 grade stainless steel 3.RAM / ROM: 2GB / 16GB 4.Display: 8" IPS LCD 5.Screen: 8" capacitive touch screen 6.Camera: 2MP camera,star light 7.Relay In/Out: 3/3 8.Card reader: 13.56MHz & 125kHz 9.RS485 & Weigand port 10.IR Sensor 11.Installation: In-wall 12.Water-proof & Dust-proof: IP65 13. IK10 14. Onvif	2,200\$
2		Akuvox X912	Vandal-resistant Door Phone 1.Size:234x94x34mm 2.front panel: Stainless steel 3.Display: 4 Inch, color TFT LCD, touchable 4.Camera: 2M pixels 5.Relays out: 2 6.RF card reader: 13.56MHz & 125kHz, NFC 7.RS485 & Weigand port 8.linux 9.Installation: Wall-mounted 10.Water-proof & Dust-proof:IP65	1300\$
3		Akuvox R29CB	SIP Android Door Phone with Facial Recognition&mask&temperture muserment 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	2,750\$
4		Akuvox R29CL	SIP Android Door Phone with Facial Recognition&FingerPriting LTE module 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	1,800\$
5		Akuvox R29CT	SIP Android Door Phone with Facial Recognition&FingerPriting 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	1,807\$
6		R29C	SIP Android Door Phone with Facial Auxiliary Camera 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	1,650\$
7		R29S	SIP Android Door Phone with Facial Standard version 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	1,336\$

Out Door Panel Door Phone Out Door Panel Door Phone Out Door Panel Door Phone Out Door Panel Door Phone Out Door Panel Door Phone

AKUVOX

Row.	Product Image	Code	Description	PRICE(\$)
8		Akuvox E16	budget-friendly face recognition door phone 1.Linux 2. Display: 5 Inch IPS LCD, 1280x720 3. Camera: 2M pixels, WDR 4.Wiegand & RS485 Port: Support 5.RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8. 802.3af Power-over-Ethernet 9. POE Or 12V DC Connector (if not using PoE) 10.Tamper: Support 11 Installation: Wall-mounted 12. Water-proof & Dust-proof:IP65 13. NFC & Bluetooth	625\$
9		Akuvox E18	budget-friendly face recognition door phone 1.Linux 2.Housing Material: Plastic 3.Display: 7 Inch IPS LCD, 1024x600 4.Camera: 2M pixels, WDR 5.Wiegand & RS485 Port: Support 6.Relay In / Out: 3 / 2 7.Bluetooth: Support 8.POE Or 12V DC Connector (if not using PoE) 9.Tamper: Support 10.Installation: Wall-mounted 11.Water-proof & Dust-proof:IP65 12.RF Card Reader: 13.56MHz,125kHz & NFC 13.Linux	885\$
10		R28A	SIP Intercom with Keypad 1.front panel material: Aluminium 2.Output Relay: 3 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Display: 4.3 Inch, color TFT LCD 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand & RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall	755\$
11		R27A	SIP Intercom with Keypad 1.front panel material: Aluminium 2.Output Relay: 3 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Wide-angle camera: 116° (H), 60° (V) 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand & RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall	495\$
12		R20k	Palm-size Door phone 1.Front panel: Aluminium alloy 2.Output Relay: 2 output relays for door opener 3.Water-proof & Dust-proof: IP65 4.Wide-angle camera: 120° 5.POE Or 12V DC Connector (if not using PoE) 6.DIM: 226x108x52mm 7.Complies with SIP standard for easy integration in every SIP PBX 8. Installation: on-wall 9.Linux 10.Onvif 11.Wiegand & RS485 port: Support 12.Card reader: 13.56MHz & 125kHz	in-Wall 418\$ on-Wall 385\$
13		Akuvox R20B-X5	Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 5 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7.Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14.POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: On-wall 17. Onvif	in-Wall 385\$ on-Wall 352\$
14		Akuvox R20B-X4	Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 4 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7.Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: On-wall 17. Onvif	in-Wall 374\$ on-Wall 341\$

Out Door Panel Door Phone Out Door Panel Door Phone Out Door Panel Door Phone Out Door Panel









AKUVOX

Row.	Product Image	Code	Description	PRICE(\$)
15		Akuvox R20B-X3	Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 3 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7. Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Onvif	in-Wall 363\$ on-Wall 330\$
16		Akuvox R20B-X2	Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 2 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7. Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Onvif	in-Wall 341\$ on-Wall 308\$
17		Akuvox R20A	single-button SIP video door phone 1. Linux 2. Body material: Aluminum 3. Camera: 3M pixels, automatic lighting, Wide-angle camera: 116° 4. RF Card Reader 13.56MHz & 125kHz Card reader 5. Output Relay: 2 output relays for door opener 6. Water-proof & Dust-proof: IP65 7. Installation: On-wall 8. POE or 12V DC Connector (if not using PoE) 9. Wiegand & RS485 port: Support 10. Complies with SIP standard for easy integration in every SIP PBX; 11. Onvif	in-Wall 300\$ on-Wall 267\$
18		Akuvox E12S	Linux single-button SIP video door phone 1. Body material: ABS plastics 2. Camera: 2M pixels with 95° angle, LED White Light 3. Output Relay: 2 output relays for door opener 4. Installation: in-wall 5. Infrared sensor 6.: 1 call button Infrared Sensor: Support RF card reader: 13.56 MHz and 125 kHz, NFC, Bluetooth 7. micro SD Card Slot: 1 8. Onvif 9. Wiegand & RS485 port: Support 10. Water-proof & Dust-proof: IP65	155\$
19		Akuvox E12W	Linux single-button SIP video door phone 1. Body material: ABS plastics 2. Camera: 2M pixels with 95° angle, LED White Light 3. Output Relay: 2 output relays for door opener 4. Installation: in-wall 5. Infrared sensor 6.: 1 call button Infrared Sensor: Support RF card reader: 13.56 MHz and 125 kHz, NFC, Bluetooth and WIFI 7. micro SD Card Slot: 1 8. Onvif 9. Wiegand & RS485 port: Support 10. Water-proof & Dust-proof: IP65	172\$
20		Akuvox E11	Linux single-button SIP video door phone 1. Body material: ABS plastics 2. Camera: 2M pixels with 95° angle, LED White Light 3. Output Relay: 2 output relays for door opener 4. Installation: on-wall 5. Infrared sensor 6.: 1 call button Infrared Sensor: Support RF card reader: 13.56 MHz and 125 kHz 7. Onvif 8. Wiegand & RS485 port: Support	204\$
21		VP-R49G	SIP based Android Video phone 1. 7" touch screen with 1024 x 600 resolution 2. Android 9.0 OS 3. Premium audio and video quality 4. DTMF for remote door opening 5. Camera: 2MP with privacy shutter 6. Built-in Bluetooth, USB, and Wi-Fi 7. Support 3rd-party apps 8. Support 2 Sip Account 9. RJ9 Handset 10. POE 11. Support Call Waiting, Call Forward, Call Transfer 12. Call on Hold, Mute, Auto-answer, Redial, DND 13. Local 3-Way Conference	550\$
22		SP-R63G	Gigabit Ethernet IP Phone 1. Dual-port Gigabit Ethernet, PoE 2. Up to 6 SIP Accounts 3. 2.8" 320 * 240 pixel color display with backlight 4. Support Call Waiting, Call Forward, Call Transfer 5. Call on Hold, Mute, Auto-answer, Redial, DND 6. Local 3-Way Conference 7. Phonebook (500 entries), Blacklist (100 entries), Call logs (100 entries) 8. 5 Remote Phone Book URL Supported 9. 39 Keys (with 4 Soft Keys, 10 Programmable keys)	175\$

Door Phone Out Door Panel Door Phone Out Door Panel Door Phone Out Door Panel Door Phone Out Door Panel Door Phone Out Door Panel

Phone

AKUVOX

Row.	Product Image	Code	Description	PRICE(\$)
23		Akuvox SIP touch Panel C319A	SIP Indoor unit (Android V ersion 9) 1.10" capacitive touch screen with energy saving mode 2. body material: plastic 3. Bluetooth, wifi, Camera 4. Powered by PoE or external source 5. Supports US or European electrical wall box mounting 6. Reception of a HD picture from the door communicator 7. IO: 8 8. Two-way communication based on SIP v2.0 protocol 9. RS485 port: Support 10. Relays out: 2 11. Installation: Wall-mounted & Desktop 12. POE or 12V DC Connector (if not using PoE)	550\$
24		Akuvox SIP Touch Panel X933W	SIP Indoor unit (Android V ersion 9) 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. Bluetooth, wifi 7. body material: plastic 8. IO: 8 9. RS485 port: Support 10. Relays out: 2 11. Installation: Wall-mounted & Desktop 12. POE or 12V DC Connector (if not using PoE)	440\$
25		Akuvox SIP Touch Panel X933S	SIP Indoor unit (Android V ersion 9) 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. body material: plastic 7. RS485 port: Support 8. Relays out: 2 9. Installation: Wall-mounted & Desktop 10. IO: 8	408\$
26		Akuvox SIP Touch Panel IT83R	Android SIP Indoor 1. front panel: Aluminum 2. 10" capacitive touch screen with energy saving mode 3. Reception of a HD picture from the door communicator 4. Two-way communication based on SIP v2.0 protocol 5. POE or 12V DC Connector (if not using PoE) 6. Supports US or European electrical wall box mounting 7. Tamper resistant design. Desktop Stand (optional) 8. Memory Slot: 1 micro SD 9. RS485 port: Support 8. Relays out: 2 9. IO: 8 10. Installation: Wall-mounted & Desktop	535\$
27		Akuvox SIP Touch Panel IT83A	Android SIP Indoor Wifi and Bluetooth & Camera: 1M pixels 1. front panel: Aluminum 2. 10" capacitive touch screen with energy saving mode 3. Reception of a HD picture from the door communicator 4. Two-way communication based on SIP v2.0 protocol 5. POE or 12V DC Connector (if not using PoE) 6. Supports US or European electrical wall box mounting 7. Tamper resistant design. Desktop Stand (optional) 8. Memory Slot: 1 micro SD 9. RS485 port: Support 8. Relays out: 2 9. IO: 8 10. Installation: Wall-mounted & Desktop	613\$
28		Akuvox SIP touch Panel IT82W	Android SIP Indoor 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. Bluetooth, and Wireless feature 7. front panel: Aluminum 8. Memory slot: 1 SD slot 9. 5 capacitive buttons, programmable 10. RS485 port: Support 11. Relays out: 1 12. IO: 8	408\$
29		Akuvox SIP touch Panel C315W	Android SIP Indoor 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. WIFI Enabled , Bluetooth 7. front panel: plastic 8. RS485 port: Support 9. Relays out: 1 10. IO: 8	297\$
30		Akuvox SIP touch Panel C315S	Android SIP Indoor 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. front panel: plastic 7. RS485 port: Support 8. Relays out: 1 9. IO: 8	267\$
31		Akuvox SIP touch Panel C313S	Linux SIP Indoor 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. front panel: plastic 7. RS485 port: Support	143\$

Indoor Monitor

Indoor Monitor








Indoor Monitor

Indoor Monitor

Indoor Monitor

Indoor Monitor

AKUVOX

Row.	Access Control	Product Image	Code	Description	PRICE(\$)
32	Access Control		A01	IP-based access control terminal that combines door controller and card reader in one device. 1. card reader: 125KHZ and 13.5MHZ RFID card and NFC 2. Aluminum frame, front panel Toughened Glass 3. Dimension: 86 x 86 x 33 (mm) 4. Wiegand 5. Tamper-proof Sensor 6. Relay out: 1 7. TCP/IP Communication 8. POE or 12V DC connector (if not using PoE) 9. Capacity: up to 10,000 card and 100,000 event logs 10. Water-proof & Dust-proof: IP65 11. Installation: on-wall or in-wall	185\$
33	Access Control		A02	IP-based access control terminal that combines door controller and card reader in one device. 1. card reader: 125KHZ and 13.5MHZ RFID card and NFC 2. Aluminum frame, front panel Toughened Glass 3. Dimension: 86 x 86 x 33 (mm) 4. Wiegand 5. Tamper-proof Sensor 6. Relay out: 1 7. TCP/IP Communication 8. POE or 12V DC connector (if not using PoE) 9. Capacity: up to 20,000 card and 100,000 event logs 10. Water-proof & Dust-proof: IP65 11. Installation: on-wall or in-wall	220\$
34	Access Control		A03	IP-based access control terminal combining a reader and a door controller. It offers flexible credentials, including wave-to-unlock via Bluetooth, mobile access via NFC, and RFID cards. 1. Front panel: Toughened Glass 2. Aluminum frame, front panel Toughened Glass 3. RFID card reader: 13.56MHz & 125KHz 4. Bluetooth: BLE5.0 5. Relay out: 1 6. Inputs: 2 7. Wiegand: Support 8. Power output: 12V 600mA 9. Water-proof & Dust-proof: IP65 10. Installation: on-wall or in-wall 11. Dimension: 86 x 86 x 33 (mm) 12. Capacity: up to 20,000 card and 100,000 event logs 13. POE or 12V DC connector (if not using PoE) 14. Water-proof & Dust-proof: IP65	260\$
35	Access Control		A092	intelligent access controller housed in a stylish SGCC cabinet 1. Front panel: SGCC 2. Support up to 50,000 cards and 100,000 event logs 3. Support RS485, OSDP, and Wiegand Protocols 4. Tamper-proof Sensor 5. Backlit Function icons 6. Support backup battery 7. Wiegand port: 4 8. Relays out: 2 9. Exit button input: 2 10. Installation: Wall-mounted 11. Dimension: 365 x 340 x 86 (mm) 12. POE or 12V 800mA per door for locks/strikes, read and input devices 13. Backup battery: Support	600\$
36	Access Control		A05S	smart access control device with facial recognition 1. 5" screen with energy saving mode, 1280x720 2. Camera: 2M pixels, WDR 3. Wiegand & RS485 Port: Support 4. NFC 5. RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8. Housing Material: Plastic 9. POE or 12V DC Connector (if not using PoE) 10. Tamper: Support 11. Installation: Wall-mounted 12. Water-proof & Dust-proof: IP65 13. Working Humidity: 10~90%, no condensing 14. Working Temperature: -20°C~+60°C 15. 20,000 face capacity & 20,000 card capacity & 50,000 event 16. face mask detection	346\$
37	Access Control		A05S+MD01	smart access control device with facial recognition wrist temperature measurement 1. 5" screen with energy saving mode, 1280x720 2. Camera: 2M pixels, WDR 3. Wiegand & RS485 Port: Support 4. NFC 5. RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8. Housing Material: Plastic 9. POE or 12V DC Connector (if not using PoE) 10. Tamper: Support 11. Installation: Wall-mounted 12. Water-proof & Dust-proof: IP65 13. Working Humidity: 10~90%, no condensing 14. Working Temperature: -20°C~+60°C 15. 20,000 face capacity & 20,000 card capacity 16. face mask detection	516\$
38	Access Control		A05S+MD02	smart access control device with facial recognition with forehead temperature measurement 1. 5" screen with energy saving mode, 1280x720 2. Camera: 2M pixels, WDR 3. Wiegand & RS485 Port: Support 4. NFC 5. RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8. Housing Material: Plastic 9. POE or 12V DC Connector (if not using PoE) 10. Tamper: Support 11. Installation: Wall-mounted 12. Water-proof & Dust-proof: IP65 13. Working Humidity: 10~90%, no condensing 14. Working Temperature: -20°C~+60°C 15. 20,000 face capacity & 20,000 card capacity 16. face mask detection	946\$

AKUVOX